Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-132-8731

#### **Inclosure Material:**

Metal

**Overall Length:** 

1.252 inches

# **Overall Height:**

0.340 inches

### **Overall Width:**

0.700 inches

#### **End Application:**

Flight set 76301

#### Mounting Facility Quantity:

2

#### Internal Configuration:

Junction contact

#### Joint Electronic Device Engineering Council/jedec/case Outline Designation:

То-66

# Electrode Internally-electrically Connected To Case:

Collector

#### **Mounting Method:**

Unthreaded hole

#### Semiconductor Material:

Silicon

#### Voltage Rating In Volts Per Characteristic:

6.0 emitter to base voltage, static, collector open and 250.0 collector to base voltage/static/emitter open and 200.0 collector to emitter voltage/static/base open

#### **Current Rating Per Characteristic:**

5.00 amperes source cutoff current and 1.00 amperes source cutoff current

#### **Power Rating Per Characteristic:**

30.0 watts small-signal input power, common-collector preset

# Maximum Operating Tempurature Per Measurement Point:

200.0 degrees celsius ambient air

# **Special Features:**

Junction pattern arrangement: npn

# Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

1 case and 2 uninsulated wire lead

# **Specification Data:**

81349-mil-prf-19500/455 government specification

# Shelf Life:

N/a

# Unit Of Measure:

# NSN 5961-01-132-8731

Transistor - Page 2 of 2



# Demilitarization:

Yes - demil/mli

Fiig:

A110a0

# Mil-std (military Standard):

Mil-prf-19500 spec.