NSN 5961-01-153-7600

Transistor - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5961-01-153-7600

Inclosure Material: Metal Overall Length: Between 0.115 inches and 0.150 inches Terminal Length: 0.500 inches Overall Diameter: Between 0.209 inches and 0.230 inches Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 30.01 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A110a0	
Overall Length:Between 0.115 inches and 0.150 inchesTerminal Length:0.500 inchesOverall Diameter:Between 0.209 inches and 0.230 inchesInternal Configuration:Field effectJoint Electronic Device Engineering Council/jedec/case Outline Designation:To-52Mounting Method:TerminalTerminal Circle Diameter:0.100 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SilionVoltage Rating In Volts Per Characteristic:30.00 milliamperes zero-gate-voltage drain currentPower Rating Per Characteristic:YaUnit Of Measure:rNoPiniltarization:NoFig:	Inclosure Material:
Between 0.115 inches and 0.150 inches Terminal Length: 0.500 inches Overall Diameter: Between 0.209 inches and 0.230 inches Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0. gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 30.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig:	Metal
Terminal Length: 0.500 inches Overall Diameter: Between 0.209 inches and 0.230 inches Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 3.0.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig:	Overall Length:
0.500 inchesOverall Diameter:Between 0.209 inches and 0.230 inchesInternal Configuration:Field effectJoint Electronic Device Engineering Council/jedec/case Outline Designation:To-52Mounting Method:TerminalTerminal Circle Diameter:0.100 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:3.0.00 milliamperes zero-gate-voltage drain currentPower Rating Per Characteristic:300.00 milliwatts total device dissipationTerminal Type And Quantity:3 uninsulated wire leadSheff Life:N/aInfo Measure:NaNicFig:	Between 0.115 inches and 0.150 inches
Overall Diameter: Between 0.209 inches and 0.230 inches Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 3.0.0 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 30.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.209 inches and 0.230 inches Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.500 inches
Internal Configuration: Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Vottage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Overall Diameter:
Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteris	Between 0.209 inches and 0.230 inches
Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Internal Configuration:
To-52 Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.00 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Field effect
Mounting Method: Terminal Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Joint Electronic Device Engineering Council/jedec/case Outline Designation:
Terminal Terminal Circle Diameter: Control Cir	To-52
Terminal Circle Diameter: 0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliawatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Method:
0.100 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Terminal
Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pomilitarization: No	Terminal Circle Diameter:
Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.100 inches
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: No Fig:	Features Provided:
Silicon Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: No Fig:	Hermetically sealed case
Voltage Rating In Volts Per Characteristic: 5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Semiconductor Material:
5.0 gate to source threshold voltage Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Silicon
Current Rating Per Characteristic: 30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Voltage Rating In Volts Per Characteristic:
30.00 milliamperes zero-gate-voltage drain current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fiig:	5.0 gate to source threshold voltage
Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Current Rating Per Characteristic:
300.0 milliwatts total device dissipation Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	30.00 milliamperes zero-gate-voltage drain current
Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Rating Per Characteristic:
3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	300.0 milliwatts total device dissipation
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	3 uninsulated wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
-	No
A110a0	Fiig:
	A110a0