Diode Semiconductor Device - Page 1 of 1



in specification

View Online at https://aerobasegroup.com/nsn/5961-01-167-3947

| Inclosure Material: | |
|---|------------------|
| Metal | |
| Overall Length: | |
| 0.800 inches | |
| Function For Which Designed: | |
| Voltage regulator | |
| Mounting Facility Quantity: | |
| 1 | |
| Joint Electronic Device Engineering Council/jedec/case Outline Designation: | |
| D0-4 | |
| Mounting Method: | |
| Threaded stud | |
| Features Provided: | |
| Hermetically sealed case | |
| Overall Width Across Flats: | |
| 0.505 inches | |
| Thread Size: | |
| 0.190 inches | |
| Semiconductor Material: | |
| Silicon | |
| Voltage Rating In Volts Per Characteristic: | |
| 23.1 collector to emitter reverse voltage, with base short-circuited to emitter | |
| Current Rating Per Characteristic: | |
| 435.00 milliamperes repetitive peak forward current | |
| Maximum Operating Tempurature Per Measurement Point: | |
| 150.0 degrees celsius case | |
| Test Data Document: | |
| 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type da | ata in specifica |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type da | ta on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Thread Series Designator: | |
| Unf | |
| Terminal Type And Quantity: | |
| 1 tab, solder lug and 1 threaded stud | |
| Specification Data: | |
| 81349-mil-s-19500/124 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A110a0 | |
| | |