NSN 5961-01-180-6740



Transistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5961-01-180-6740 **Inclosure Material:** Metal **Overall Length:** 1.573 inches **Overall Height:** 0.360 inches **Overall Width:** 1.050 inches **Mounting Facility Quantity: Internal Configuration:** Field effect Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-204aa **Electrode Internally-electrically Connected To Case: Mounting Method:** Unthreaded hole **Semiconductor Material:** Silicon Voltage Rating In Volts Per Characteristic: 500.0 drain to source voltage and 500.0 drain to gate voltage and 20.0 gate to source voltage **Current Rating Per Characteristic:** 12.00 amperes source current and 48.00 amperes off-state current, peak **Power Rating Per Characteristic:** 150.0 watts total power dissipation **Maximum Operating Tempurature Per Measurement Point:** 150.0 degrees celsius junction **Test Data Document:** 81349-mil=prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead and 1 case **Specification Data:** 81349-mil-prf-19500/543 government specification

Demilitarization: No

Unit Of Measure:

Shelf Life:

N/a

Fiig: A110a0

NSN 5961-01-180-6740

Transistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-19500 spec.