

View Online at <https://aerobasegroup.com/nsn/5961-01-215-7482>

Inclosure Material:

Metal

Overall Length:

1.252 inches

Overall Height:

0.340 inches

Overall Width:

0.700 inches

Mounting Facility Quantity:

2

Internal Configuration:

Junction contact-darlington connected

Joint Electronic Device Engineering Council/jedec/case Outline Designation:

To-66

Electrode Internally-electrically Connected To Case:

Collector

Mounting Method:

Unthreaded hole

Features Provided:

Hermetically sealed case and quality assurance level tx

Semiconductor Material:

Silicon

Voltage Rating In Volts Per Characteristic:

60.0 collector to base voltage/static/emitter open and 5.0 emitter to base voltage, static, collector open and 60.0 collector to emitter voltage/static/base open

Current Rating Per Characteristic:

8.00 amperes source cutoff current and 120.00 milliamperes source cutoff current

Power Rating Per Characteristic:

75.0 watts small-signal input power, common-collector preset

Transfer Ratio:

350.0 small-signal short-circuit forward current transfer ratio, common-emitter

Maximum Operating Temperature Per Measurement Point:

175.0 degrees celsius ambient air

Special Features:

Junction pattern arrangement: pnp

Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 pin and 1 case

Specification Data:

81349-mil-prf-19500/540 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.