## NSN 5961-01-225-9701

Transistor - Page 1 of 1

**AeroBase** 

View Online at https://aerobasegroup.com/nsn/5961-01-225-9701

Inclosure Material: Plastic Plastic Overall Length: Between 0.240 inches and 0.260 inches Terminal Length: 1.500 inches Overall Diameter: 0.370 inches Overall Diameter: 0.370 inches End Application: Aircraft model sh-60b lamps mark 3 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 10.00 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Emilitarization:
Overall Length:         Between 0.240 inches and 0.260 inches         Terminal Length:         1.500 inches         Overall Diameter:         0.370 inches         End Application:         Aircraft model sh-60b lamps mark 3         Mounting Method:         Terminal         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         10.00 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open         Current Rating Per Characteristic:         10.00 microamperes zero-gate-voltage source current preset         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius ambient air         Terminal Type And Quantity:         3 uninsulated wire lead         Shif Life:         N/a         Unit Of Measure:         Init Of Measure:         Init Of Measure:         Init Of Measure:
Between 0.240 inches and 0.260 inches         Terminal Length:         1.500 inches         Overall Diameter:         0.370 inches         End Application:         Aircraft model sh-60b lamps mark 3         Mounting Method:         Terminal         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         10.00 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open         Current Rating Per Characteristic:         10.00 microamperes zero-gate-voltage source current preset         Maximum Operating Tempurature Per Measurement Point:         20.00 degrees celsius ambient air         Terminal Type And Quantity:         3 uninsulated wire lead         Shelf Life:         N/a         Unit Of Measure:         Init Of Measure:         Init Of Measure:         Init Of Measure:
Terminal Length: 1.500 inches Overall Diameter: 0.370 inches End Application: Aircraft model sh-60b lamps mark 3 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: -
<ul> <li>1.500 inches</li> <li>Overall Diameter:</li> <li>0.370 inches</li> <li>End Application:</li> <li>Aitcraft model sh-60b lamps mark 3</li> <li>Mounting Method:</li> <li>Terminal</li> <li>Semiconductor Material:</li> <li>Silicon</li> <li>Voltage Rating In Volts Per Characteristic:</li> <li>100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open</li> <li>Current Rating Per Characteristic:</li> <li>10.00 microamperes zero-gate-voltage source current preset</li> <li>Maximum Operating Tempurature Per Measurement Point:</li> <li>200.0 degrees celsius ambient air</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> <li>Sheff Life:</li> <li>N/a</li> <li>Unit Of Measure:</li> <li>-</li> </ul>
Overall Diameter:0.370 inchesEnd Application:Aircraft model sh-60b lamps mark 3Mounting Method:TerminalSemiconductor Material:SoliconVoltage Rating In Volts Per Characteristic:100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector openMaximum Operating Tempurature Per Measurement Point:200.0 digrees celsius ambient airTerminal Type And Quantity:3 uninsulated wire leadShelf Life:N/aUnit Of Measure:
0.370 inches End Application: Aircraft model sh-60b lamps mark 3 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
End Application:         Aicreaft model sh-60b lamps mark 3         Mounting Method:         Terminal         Semiconductor Material:         Solicon         Voltage Rating In Volts Per Characteristic:         100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open         Current Rating Per Characteristic:         10.00 microamperes zero-gate-voltage source current preset         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius ambient air         Terminal Type And Quantity:         3 uninsulated wire lead         Shelf Life:         N/a         Unit Of Measure:         T
Aircraft model sh-60b lamps mark 3 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset 10.00 microamperes zero-gate-voltage source current preset 200.0 degrees celsius ambient air 200.0 degrees celsius ambient air 200.0 degrees celsius ambient air Shelf Life: N/a Unit Of Measure:
Mounting Method:         Terminal         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open         Current Rating Per Characteristic:         10.00 microamperes zero-gate-voltage source current preset         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius ambient air         Terminal Type And Quantity:         3 uninsulated wire lead         Shelf Life:         N/a         Unit Of Measure:
Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air 200.0 degrees celsius ambient air Si uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset 10.00 degrees celsius ambient air 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Silicon Voltage Rating In Volts Per Characteristic: 100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air 200.0 degrees celsius ambient air 200.0 degrees celsius ambient air 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Voltage Rating In Volts Per Characteristic:100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector openCurrent Rating Per Characteristic:10.00 microamperes zero-gate-voltage source current presetMaximum Operating Tempurature Per Measurement Point:200.0 degrees celsius ambient airTerminal Type And Quantity:3 uninsulated wire leadShelf Life:N/aUnit Of Measure:-
100.0 collector to emitter voltage/static/base open and 8.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Current Rating Per Characteristic: 10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
10.00 microamperes zero-gate-voltage source current preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
200.0 degrees celsius ambient air Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: 
Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure: 
Unit Of Measure:
Demilitarization:
No
Fiig:
A110a0