# NSN 5961-01-235-2202

Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-235-2202

# Inclosure Material:

Metal

**Overall Length:** 

0.260 inches

# Terminal Length:

0.500 inches

# **Overall Diameter:**

0.370 inches

### Internal Configuration:

Junction contact

# Joint Electronic Device Engineering Council/jedec/case Outline Designation:

#### To-39

Electrode Internally-electrically Connected To Case:

#### Collector

**Mounting Method:** 

# Terminal

Terminal Circle Diameter:

#### 0.000 : 1

0.200 inches

#### Features Provided:

Hermetically sealed case and quality assurance level s

#### Semiconductor Material:

Silicon

#### Voltage Rating In Volts Per Characteristic:

60.0 collector to base voltage/static/emitter open and 30.0 collector to emitter voltage/static/base open and 3.5 emitter to base voltage, static, collector open

#### **Current Rating Per Characteristic:**

0.40 amperes source cutoff current

#### **Power Rating Per Characteristic:**

1.0 watts small-signal input power, common-collector preset

#### Transfer Ratio:

15.0 static forward current transfer ratio, common-emitter and 200.0 static forward current transfer ratio, common-emitter

# Maximum Operating Tempurature Per Measurement Point:

175.0 degrees celsius junction

#### **Special Features:**

Junction pattern arrangement: npn

# Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 uninsulated wire lead

#### Specification Data:

81349-mil-prf-19500/398 government specification

# Shelf Life:

NI/o

# NSN 5961-01-235-2202

Transistor - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.

