Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-235-3273

### **Inclosure Material:**

Metal

**Overall Length:** 

1.573 inches

# **Overall Height:**

0.450 inches

### **Overall Width:**

1.050 inches

### **Mounting Facility Quantity:**

2

### Internal Configuration:

Junction contact

# Joint Electronic Device Engineering Council/jedec/case Outline Designation:

#### To-3

# Electrode Internally-electrically Connected To Case:

Collector

### Mounting Method:

Unthreaded hole

### **Features Provided:**

Hermetically sealed case and quality assurance level s

# Semiconductor Material:

Silicon

# Voltage Rating In Volts Per Characteristic:

150.0 collector to base voltage/static/emitter open and 120.0 collector to emitter voltage/static/base open and 7.0 emitter to base voltage,

static, collector open

## **Current Rating Per Characteristic:**

30.00 amperes source cutoff current and 10.00 amperes source cutoff current

# **Power Rating Per Characteristic:**

140.0 watts small-signal input power, common-collector preset

#### Transfer Ratio:

20.0 static forward current transfer ratio, common-emitter and 100.0 static forward current transfer ratio, common-emitter

# Maximum Operating Tempurature Per Measurement Point:

200.0 degrees celsius junction

#### **Special Features:**

Junction pattern arrangement: npn

#### **Test Data Document:**

81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 pin and 1 case

**Specification Data:** 

81349-mil-s-19500/488 government specification

Shelf Life:

NI/o

# NSN 5961-01-235-3273

Transistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A110a0