

View Online at <https://aerobasegroup.com/nsn/5961-01-235-4121>

**Inclosure Material:**

Metal

**Overall Length:**

1.252 inches

**Overall Height:**

0.340 inches

**Overall Width:**

0.700 inches

**Mounting Facility Quantity:**

2

**Internal Configuration:**

Junction contact

**Joint Electronic Device Engineering Council/jedec/case Outline Designation:**

To-66

**Electrode Internally-electrically Connected To Case:**

Collector

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Hermetically sealed case and quality assurance level s

**Semiconductor Material:**

Silicon

**Voltage Rating In Volts Per Characteristic:**

250.0 collector to base voltage/static/emitter open and 200.0 collector to emitter voltage/static/base open and 6.0 emitter to base voltage, static, collector open

**Current Rating Per Characteristic:**

5.00 amperes source cutoff current and 1.00 amperes source cutoff current

**Power Rating Per Characteristic:**

30.0 watts small-signal input power, common-collector preset

**Transfer Ratio:**

40.0 static forward current transfer ratio, common-emitter and 120.0 static forward current transfer ratio, common-emitter

**Maximum Operating Temperature Per Measurement Point:**

200.0 degrees celsius ambient air

**Special Features:**

Junction pattern arrangement: npn

**Test Data Document:**

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 pin and 1 case

**Specification Data:**

81349-mil-prf-19500/455 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A110a0

**Mil-std (military Standard):**

Mil-prf-19500 spec.