# NSN 5961-01-254-5043

Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-254-5043 **Inclosure Material:** Metal **Overall Length:** 0.210 inches **Terminal Length:** 0.500 inches **Overall Diameter:** 0.230 inches **Internal Configuration:** Junction contact Joint Electronic Device Engineering Council/jedec/case Outline Designation: To-18 **Electrode Internally-electrically Connected To Case:** Collector **Mounting Method: Terminal Terminal Circle Diameter:** 0.100 inches **Features Provided:** Hermetically sealed case and quality assurance level tx **Semiconductor Material:** Silicon Voltage Rating In Volts Per Characteristic: 40.0 collector to base voltage/static/emitter open and 40.0 collector to emitter voltage, dc with base short-circuited to emitter and 20.0 collector to emitter voltage/static/base open and 6.0 emitter to base voltage, static, collector open **Power Rating Per Characteristic:** 1.2 watts small-signal input power, common-collector preset **Maximum Operating Tempurature Per Measurement Point:** 

200.0 degrees celsius junction

#### **Special Features:**

Junction pattern arrangement: npn

# **Test Data Document:**

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 uninsulated wire lead

# **Specification Data:**

81349-mil-s-19500/317 government specification

#### Shelf Life:

N/a

### **Unit Of Measure:**

--

# Demilitarization:

Vec - demil/mli

# NSN 5961-01-254-5043

Transistor - Page 2 of 2



Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.