NSN 5961-01-273-3054

Thyristor Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-273-3054
Inclosure Material:
Metal
Overall Length:
0.210 inches
Terminal Length:
0.500 inches
Overall Diameter:
0.230 inches
Internal Configuration:
Junction contact
Joint Electronic Device Engineering Council/jedec/case Outline Designation:
To-18
Mounting Method:
Terminal
Terminal Circle Diameter:
0.110 inches
Features Provided:
Hermetically sealed case
Semiconductor Material:
Silicon
Silicon
Silicon Voltage Rating In Volts Per Characteristic:
Silicon Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage
Silicon Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic:
Silicon Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point:
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features:
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity:
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life:
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Voltage Rating In Volts Per Characteristic: 100.0 repetitive peak off-state voltage and 100.0 repetitive peak reverse voltage Current Rating Per Characteristic: 6.00 amperes forward current, total rms torr Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Special Features: Junction pattern arrangement: pnpn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: