## NSN 5961-01-298-5989

Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-298-5989

| Inclosure Material:   |
|---|
| Metal   |
| Overall Length:   |
| 0.520 inches  |
| Terminal Length:  |
| 0.312 inches  |
| Overall Diameter:   |
| 1.250 inches  |
| End Application:  |
| Velocity pool reparable piece parts; aircraft, tomcat f-14  |
| Mounting Facility Quantity:   |
| 1   |
| Internal Configuration:   |
| Junction contact  |
| Joint Electronic Device Engineering Council/jedec/case Outline Designation:   |
| To-36   |
| Electrode Internally-electrically Connected To Case:  |
| Collector   |
| Mounting Method:  |
| Terminal and unthreaded hole  |
| Features Provided:  |
| Hermetically sealed case  |
| Criticality Code Justification:   |
| Feat  |
| Semiconductor Material:   |
| Silicon   |
| Voltage Rating In Volts Per Characteristic:   |
| 500.0 collector to base voltage/static/emitter open and 500.0 collector to emitter voltage/static/base open and 6.8 emitter to base voltage |
| static, collector open  |
| Current Rating Per Characteristic:  |
| 10.00 amperes source cutoff current and 3.00 amperes source cutoff current  |
| Power Rating Per Characteristic:  |
| 150.0 watts small-signal input power, common-collector  |
| Transfer Ratio:   |
| 7.0 static forward current transfer ratio, common-emitter and 20.0 static forward current transfer ratio, common-emitter                    |
| Maximum Operating Tempurature Per Measurement Point:  |
| 150.0 degrees celsius ambient air   |
| Special Features:   |
| Weapon system essential; junction pattern arrangement: npn  |
| Terminal Type And Quantity:   |

N/a

Shelf Life:

2 uninsulated wire lead and 1 threaded stud

## NSN 5961-01-298-5989

Transistor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A110a0