

View Online at <https://aerobasegroup.com/nsn/5961-01-316-3455>

**Inclosure Material:**

Metal

**Overall Length:**

Between 0.240 inches and 0.260 inches

**Terminal Length:**

Between 0.500 inches and 0.750 inches

**Overall Diameter:**

Between 0.335 inches and 0.370 inches

**Function For Which Designed:**

Amplifier and switching

**End Application:**

1440-01-269-5849 launcher, tubular, guided missile

**Internal Configuration:**

Junction contact

**Mounting Method:**

Terminal

**Terminal Circle Diameter:**

0.200 inches

**Semiconductor Material:**

Silicon

**Voltage Rating In Volts Per Characteristic:**

175.0 collector to base voltage/static/emitter open and 175.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open

**Current Rating Per Characteristic:**

1.00 amperes source cutoff current

**Power Rating Per Characteristic:**

5.0 watts small-signal input power, common-collector preset

**Maximum Operating Temperature Per Measurement Point:**

200.0 degrees celsius junction

**Special Features:**

Junction pattern arrangement: pnp

**Test Data Document:**

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 uninsulated wire lead

**Specification Data:**

81349-mil-prf-19500/357 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A110a0

**Mil-std (military Standard):**

Mil-prf-19500 spec.