

View Online at <https://aerobasegroup.com/nsn/5961-01-335-8187>

**Inclosure Material:**

Metal

**Overall Length:**

Between 0.140 inches and 0.260 inches

**Terminal Length:**

Between 1.500 inches and 1.750 inches

**Overall Diameter:**

Between 0.335 inches and 0.370 inches

**Joint Electronic Device Engineering Council/jedec/case Outline Designation:**

To-99

**Electrode Internally-electrically Connected To Case:**

Collector

**Component Name And Quantity:**

2 transistor

**Mounting Method:**

Terminal

**Terminal Circle Diameter:**

0.200 inches

**Features Provided:**

Hermetically sealed case

**Semiconductor Material:**

Silicon all transistor

**Voltage Rating In Volts Per Characteristic:**

70.0 collector to base voltage/static/emitter open all transistor and 60.0 collector to emitter voltage/static/base open all transistor and 6.0 emitter to base voltage, static, collector open all transistor

**Current Rating Per Characteristic:**

30.00 milliamperes source cutoff current all transistor

**Power Rating Per Characteristic:**

1.25 watts small-signal input power, common-collector preset all transistor

**Transfer Ratio:**

0.9 static forward current transfer ratio, common-emitter all transistor and 1.0 static forward current transfer ratio, common-emitter all transistor

**Maximum Operating Temperature Per Measurement Point:**

200.0 degrees celsius junction

**Special Features:**

All transistor junction pattern arrangement: npn

**Test Data Document:**

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A110a0

**Mil-std (military Standard):**

Mil-prf-19500 spec.