Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-363-4298

GlassOverall Length:4.850 inchesOverall Diameter:1.580 inchesMounting Method:TerminalSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:8.2 regulator voltage, dc and 6.0 reverse voltage, dcVoltage Tolerance In Percent:-5.0/+5.0Current Rating Per Characteristic:10.0 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward currentPower Rating Per Characteristic:400.0 milliwatts any acceptable universalTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aInt Of Measure:-NoFing:Alt0a0	Inclosure Material:	
4.850 inches Overall Diameter: 1.580 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Glass	
Overall Diameter: 1.580 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fig:	Overall Length:	
1.580 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	4.850 inches	
Mounting Method:TerminalSemiconductor Material:SoliconVoltage Rating In Volts Per Characteristic:8.2 regulator voltage, dc and 6.0 reverse voltage, dcVoltage Tolerance In Percent:-5.0/+5.0Current Rating Per Characteristic:1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward currentPower Rating Per Characteristic:400.0 milliwatts any acceptable universalTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit of Measure:Pomilitarization:NoFig:	Overall Diameter:	
Terminal Semiconductor Material: Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: 4.5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.580 inches	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliwatts any acceptable universal 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Liti Of Measure: - Demilitarization: No Fig:	Mounting Method:	
Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal You milliwatts any acceptable universal Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal	
Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Semiconductor Material:	
 8.2 regulator voltage, dc and 6.0 reverse voltage, dc Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: 	Silicon	
Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Voltage Rating In Volts Per Characteristic:	
-5.0/+5.0 Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal 400.0 milliwatts any acceptable universal 2 uninsulated wire lead 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	8.2 regulator voltage, dc and 6.0 reverse voltage, dc	
Current Rating Per Characteristic: 1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Life: 	Voltage Tolerance In Percent:	
1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-5.0/+5.0	
Power Rating Per Characteristic: 400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Current Rating Per Characteristic:	
400.0 milliwatts any acceptable universal Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.00 milliamperes drain current any acceptable and 47.00 milliamperes repetitive peak for	rward current
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Power Rating Per Characteristic:	
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	400.0 milliwatts any acceptable universal	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A110a0	Fiig:	
	A110a0	