NSN 5961-01-420-7747

A110a0

Thyristor Semiconductor Device - Page 1 of 1



| - | |
|---|-----|
| View Online at https://aerobasegroup.com/nsn/5961-01-420-7747 | |
| Inclosure Material: | |
| Metal | |
| Overall Length: | |
| Between 0.240 inches and 0.260 inches | |
| Terminal Length: | |
| 1.500 inches | |
| Overall Diameter: | |
| Between 0.335 inches and 0.370 inches | |
| Mounting Method: | |
| Terminal | |
| Semiconductor Material: | |
| Silicon | |
| Voltage Rating In Volts Per Characteristic: | |
| 600.0 repetitive peak reverse voltage and 600.0 repetitive peak off-state voltage and 600.0 nonrepetitive peak reverse voltage and 6. | 0 |
| peak gate voltage | |
| Current Rating Per Characteristic: | |
| 1.60 amperes forward current, total rms horsepower metric and 1.00 amperes forward current, total rms universal and 120.00 ampere | s |
| peak forward surge current nanoamperes | |
| Power Rating Per Characteristic: | |
| 0.1 watts small-signal input power, common-collector blank and 0.01 watts small-signal input power, common-collector universal | |
| Maximum Operating Tempurature Per Measurement Point: | |
| 125.0 degrees celsius ambient air | |
| Test Data Document: | |
| 96214-2693140 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, | etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) | |
| Terminal Type And Quantity: | |
| 3 uninsulated wire lead | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiia: | |