## NSN 5961-01-482-4631

Transistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5961-01-482-4631  |
|--|
| Inclosure Material:  |
| Metal  |
| Overall Length:  |
| Between 0.160 inches and 0.180 inches  |
| Terminal Length:   |
| Between 0.500 inches and 0.750 inches  |
| Overall Diameter:  |
| Between 0.340 inches and 0.370 inches  |
| Mounting Facility Quantity:  |
| 1  |
| Internal Configuration:  |
| Field effect   |
| Mounting Method:   |
| Terminal   |
| Features Provided:   |
| Radiation hardened   |
| Criticality Code Justification:  |
| Feat   |
| Semiconductor Material:  |
| Silicon  |
| Voltage Rating In Volts Per Characteristic:  |
| 200.0 drain to gate voltage and 200.0 drain to source voltage and 2.0 gate to source threshold voltage and 4.0 gate to source threshold        |
| voltage  |
| Current Rating Per Characteristic:   |
| 5.50 amperes source current and 22.00 amperes off-state current, peak  |
| Power Rating Per Characteristic:   |
| 25.0 watts average on-state power dissipation  |
| Maximum Operating Tempurature Per Measurement Point:   |
| 150.0 degrees celsius case   |
| Special Features:  |
| Electrostatic discharge sensitive and radiation hardened   |
| Nuclear Hardness Critical Feature:   |
| Hardened   |
| Test Data Document:  |
| 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Terminal Type And Quantity:  |
| 3 pin  |
| Specification Data:  |
| 81349-mil-prf-19500/601 professional/industrial association specification  |

Unit Of Measure:

Shelf Life:

N/a

## NSN 5961-01-482-4631

Transistor - Page 2 of 2



Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.