

View Online at https://aerobasegroup.com/nsn/5961-01-645-1096

	II Length:
28.5 m	illimeters
Overal	II Height:
10.0 m	illimeters
Overal	ll Width:
28.5 m	illimeters
Opera	ting Tempurature Range:
-40.0 to	o 150.0 degrees celsius
Circuit	t Connection Style Designator:
Bridge	3 phase
Absolu	ute Maximum Voltage Rating In Volts Per Characteristic:
1700.0	nonrepetitive peak reverse voltage, peak total value and 1600.0 repetitive peak reverse voltage, peak total value
Absolu	ute Maximum Current Rating Per Characteristic:
35.0 ar	mperes forward current, dc and 475.0 amperes forward current, nonrepetitive, peak total value
Mount	ing Method:
Plug-in	n terminal
Featur	res Provided:
Rohs c	directive compliance
Produ	ct Name:
Bridge	rectifier power module
Specia	al Features:
Solder	able using lead-free solder; solder alloy sn/ag/cu; universal, 3 way terminals: push-on, wrap around or solder high thermal
conduc	ctivity package, electrically insulated case; forward continuous current: 500a; forward voltage drop: 1.19v; diode type: three phase
Materia	al:
Silicon	
Precio	ous Material And Location:
Goldpl	ated leads gold
Termir	nal Type And Quantity:
5 termi	inal lug
Shelf L	Life:
N/a	
Unit O	f Measure:
Demili	tarization:
No	
Fiig:	
A503h	0