# NSN 5962-00-001-7448

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-001-7448

## **Body Length:**

Between 0.660 inches and 0.785 inches

# **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

187.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and medium power and medium speed and edge triggered and resettable

#### **Inclosure Material:**

# Ceramic and glass

# **Inclosure Configuration:**

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

4 input

#### Case Outline Source And Designator:

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### Time Rating Per Chacteristic:

70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

82577-928653 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0