NSN 5962-00-004-2131



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-004-2131 **Body Length:** Between 0.240 inches and 0.280 inches **Body Width:** Between 0.120 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and w/field effect transistor switch **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 channel **Design Function And Quantity:** 1 switch, analog and 1 switch, driver **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source **Time Rating Per Chacteristic:** 2500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932245 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0