NSN 5962-00-004-6357

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-004-6357

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

1000.0 milliwatts

Operating Tempurature Range:

+0.0/+70.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and adjustable and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 regulator, tracking and 2 regulator, voltage

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

30.0 volts power source

Time Rating Per Chacteristic:

40000.00 nanoseconds propagation delay time, low to high level output and 40000.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

01534-37270220 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5962-00-004-6357

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0