## NSN 5962-00-006-3084

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-00-006-3064
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.240 inches and 0.260 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and negative outputs and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
3 input
Design Function And Quantity:
1 switch, analog
Case Outline Source And Designator:
T0-5 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low leve
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
50985-8050001883 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A458a0

Demilitarization: Yes - demil/mli