

View Online at <https://aerobasegroup.com/nsn/5962-00-006-7343>

Body Length:

Between 0.240 inches and 0.275 inches

Body Width:

Between 0.160 inches and 0.185 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

120.0 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+200.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and medium power and medium speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 driver, line

Case Outline Source And Designator:

T0-85 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

27963-57530900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0