

View Online at <https://aerobasegroup.com/nsn/5962-00-006-9173>

**Body Length:**

Between 0.240 inches and 0.275 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

300.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and high gain and adjustable and negative outputs and positive outputs

**Inclosure Material:**

Ceramic and metal

**Inclosure Configuration:**

Flat pack

**Input Circuit Pattern:**

5 input

**Design Function And Quantity:**

1 amplifier, dc and 1 amplifier, wideband

**Case Outline Source And Designator:**

T0-86 joint electron device engineering council

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Test Data Document:**

03640-6088492 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0