## NSN 5962-00-007-0963

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-007-0963 **Body Length:** 0.265 inches **Body Width:** 0.265 inches **Body Height:** Between 0.030 inches and 0.080 inches **Maximum Power Dissipation Rating:** 88.0 milliwatts **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+200.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nand-nor **Case Outline Source And Designator:** T0-86 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 05869-717310-47 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

## **NSN 5962-00-007-0963**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0