

View Online at <https://aerobasegroup.com/nsn/5962-00-007-0991>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.240 inches and 0.260 inches

**Maximum Power Dissipation Rating:**

800.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and adjustable

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

4 input

**Design Function And Quantity:**

1 regulator, voltage

**Case Outline Source And Designator:**

T0-96 joint electron device engineering council

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

9.5 volts power source and 40.0 volts power source

**Time Rating Per Characteristic:**

20000.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Test Data Document:**

30003-247as-c1891 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

10 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0