NSN 5962-00-007-0991

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-007-0991

view Offilite at https://defobasegroup.com/hsh/0302-00-007-0331
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.240 inches and 0.260 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and adjustable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 regulator, voltage
Case Outline Source And Designator:
T0-96 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
9.5 volts power source and 40.0 volts power source
Time Rating Per Chacteristic:
20000.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
30003-247as-c1891 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-00-007-0991 Linear Microcircuit - Page 2 of 2



Fiig:

A458a0