## NSN 5962-00-007-4077

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-007-4077

**Body Length:** 0.796 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 268.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and resettable and edge triggered **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 counter, divide by eight **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

14 printed circuit

**Specification Data:** 

81349-mil-m-38510/13 government specification

Shelf Life:

N/a

## **NSN 5962-00-007-4077**Digital Microcircuit - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

Yes - demil/mli

Fiig:

A458a0