

View Online at <https://aerobasegroup.com/nsn/5962-00-007-4078>

**Body Length:**

0.796 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

792.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and w/totem pole output

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

2.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, low to high level output and 2.00 nanoseconds propagation delay time, high to low level output and 16.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Specification Data:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0