NSN 5962-00-007-7811

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-007-7811

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and high gain and high speed and fixed and adjustable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 amplifier, differential and 1 amplifier, video and 1 amplifier, wideband
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Tin
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
82577-932215 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: