## **NSN 5962-00-007-7820**Digital Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-00-007-7820   |
|---|
| Body Length:  |
| Between 0.240 inches and 0.275 inches   |
| Body Width:   |
| Between 0.240 inches and 0.260 inches   |
| Body Height:  |
| Between 0.030 inches and 0.070 inches   |
| Maximum Power Dissipation Rating:   |
| 250.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+175.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and positive outputs and expandable and medium speed   |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Flat pack   |
| Output Logic Form:  |
| Transistor-transistor logic   |
| Input Circuit Pattern:  |
| Dual 5 input  |
| Design Function And Quantity:   |
| 2 gate, and-or  |
| Case Outline Source And Designator:   |
| T0-86 joint electron device engineering council   |
| Terminal Surface Treatment:   |
| Gold  |
| Voltage Rating And Type Per Characteristic:   |
| -1.5 volts power source and 5.5 volts power source  |
| Precious Material And Location:   |
| Terminals gold  |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 99971-7531398 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Terminal Type And Quantity:   |
| 14 flat leads   |
| Shelf Life:   |
| N/a   |

**Unit Of Measure:** 

## NSN 5962-00-007-7820

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0