## NSN 5962-00-007-7821

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-007-7821

view Offilite at https://defobasegroup.com/hist//0302-00-007-7021
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and high speed and negative outputs and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
3 input
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-22.0 volts power source and 22.0 volts power source
Time Rating Per Chacteristic:
12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
82577-934221 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0