

View Online at <https://aerobasegroup.com/nsn/5962-00-007-7850>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and fixed and high gain and high speed and adjustable

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

6 input

Design Function And Quantity:

1 amplifier, differential and 1 amplifier, video and 1 amplifier, wideband

Case Outline Source And Designator:

T0-100 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-6.0 volts power source and 6.0 volts power source

Time Rating Per Characteristic:

10.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

05869-710200-13 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0