## NSN 5962-00-007-7854

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-007-7854

| View Online at https://aerobasegroup.com/nsn/5962-00-007-7854  |
|--|
| Body Length:   |
| Between 0.240 inches and 0.275 inches  |
| Body Width:  |
| Between 0.240 inches and 0.260 inches  |
| Body Height:   |
| Between 0.030 inches and 0.070 inches  |
| Maximum Power Dissipation Rating:  |
| 44.0 milliwatts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+200.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and positive outputs and high speed   |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Flat pack  |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| Dual 4 input   |
| Design Function And Quantity:  |
| 2 gate, nand-nor   |
| Case Outline Source And Designator:  |
| T0-86 joint electron device engineering council  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -1.5 volts power source and 5.0 volts power source   |
| Time Rating Per Chacteristic:  |
| 13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level |
| output   |
| Test Data Document:  |
| 05869-717310-37 standard (includes industry or association standards, individual manufactureer standards, etc.).                   |
| Terminal Type And Quantity:  |
| 14 flat leads  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

**Demilitarization:** Yes - demil/mli

## **NSN 5962-00-007-7854**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0