NSN 5962-00-007-7862

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-007-7862

View Offline at https://derobasegroup.com/his//0902-007002
Body Length:
Between 0.550 inches and 0.650 inches
Body Width:
Between 0.300 inches and 0.400 inches
Body Height:
Between 0.008 inches and 0.120 inches
Maximum Power Dissipation Rating:
175.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and high speed and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 decoder, one of sixteen line
Case Outline Source And Designator:
-0-019-aa joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
$05869 \hbox{-} 717360 \hbox{-} 15 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$
Terminal Type And Quantity:
24 flat leads
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-00-007-7862

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0