NSN 5962-00-008-6860

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-008-6860 **Body Length:** Between 0.330 inches and 0.350 inches **Body Width:** Between 0.140 inches and 0.275 inches **Body Height:** Between 0.050 inches and 0.080 inches **Maximum Power Dissipation Rating:** 175.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/enable and presettable and resettable and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 shift register, serial in, serial out **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminals gold and body gold **Test Data Document:** 80063-sm-b-586414 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-00-008-6860Digital Microcircuit - Page 2 of 2



Fiig:

A458a0