NSN 5962-00-009-1343Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-009-1343
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/totem pole output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter, digital
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
10236-7100037 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-00-009-1343Digital Microcircuit - Page 2 of 2



Fiig:

A458a0