# NSN 5962-00-009-6370

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-009-6370

## **Body Length:**

0.381 inches

## **Body Width:**

Between 0.140 inches and 0.275 inches

# **Body Height:**

0.080 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and edge triggered and monolithic and negative edge triggered and positive outputs and complementary outputs

#### **Inclosure Material:**

Glass and metal

#### Inclosure Configuration:

Flat pack

### **Output Logic Form:**

Transistor-transistor logic

### Input Circuit Pattern:

3 input

## **Time Rating Per Chacteristic:**

70.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

#### **Special Features:**

Formed ribbon leads

### **Precious Material And Location:**

Body gold and terminals gold

#### **Precious Material:**

Gold

### Test Data Document:

80063-sm-b-586417 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0