# NSN 5962-00-009-6372

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-009-6372

## **Body Length:**

Between 0.250 inches and 0.260 inches

## **Body Width:**

Between 0.140 inches and 0.260 inches

## **Body Height:**

0.080 inches

**Maximum Power Dissipation Rating:** 

200.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and high speed and low level

#### **Inclosure Material:**

## Ceramic and glass

Inclosure Configuration:

Flat pack

### Input Circuit Pattern:

2 input

### **Design Function And Quantity:**

1 comparator, voltage, differential

# **Terminal Surface Treatment:**

Tin

## Time Rating Per Chacteristic:

40.00 nanoseconds propagation delay time, low to high level output

### **Test Data Document:**

80063-sm-b-586434 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0