NSN 5962-00-011-2535

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-011-2535

View Online at https://aerobasegroup.com/nsn/5962-00-011-2535
Body Length:
Between 0.750 inches and 0.795 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
Between 0.120 inches and 0.195 inches
Maximum Power Dissipation Rating:
50.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 register, storage and 1 selector, data
Case Outline Source And Designator:
-0-001-ag joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Fiig: A458a0

Yes - demil/mli