NSN 5962-00-011-2762

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-011-2762

view Offiline at https://defobasegroup.com/hsh/3302-00-011-2702
Body Length:
Between 0.815 inches and 0.890 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.155 inches and 0.180 inches
Maximum Power Dissipation Rating:
550.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs and darlington-connected
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 adder, full, binary
Case Outline Source And Designator:
-0-001-al joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
24.00 nanoseconds propagation delay time, low to high level output and 24.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Terminal Type And Quantity:
16 printed circuit
Shelf Life:

-

N/a

Unit Of Measure:

NSN 5962-00-011-2762

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0