## NSN 5962-00-018-0313

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-018-0313

| view Online at https://aerobasegroup.com/nsn/5962-00-016-0313   |
|---|
| Body Length:  |
| Between 0.240 inches and 0.275 inches   |
| Body Width:   |
| Between 0.140 inches and 0.275 inches   |
| Body Height:  |
| Between 0.030 inches and 0.070 inches   |
| Maximum Power Dissipation Rating:   |
| 500.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Monolithic and hermetically sealed and positive outputs and expandable and medium speed   |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Flat pack   |
| Output Logic Form:  |
| Diode-transistor logic  |
| Input Circuit Pattern:  |
| Dual 4 input  |
| Design Function And Quantity:   |
| 2 expander  |
| Terminal Surface Treatment:   |
| Gold  |
| Voltage Rating And Type Per Characteristic:   |
| -1.5 volts power source and 5.5 volts power source  |
| Precious Material And Location:   |
| Terminal surface gold   |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 88818-c528000260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                     |
| Terminal Type And Quantity:   |
| 14 flat leads   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure   |

**Demilitarization:** Yes - demil/mli

## **NSN 5962-00-018-0313**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0