NSN 5962-00-021-3143

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-021-3143

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 50.0 milliwatts |
| Operating Tempurature Range: |
| -15.0/+55.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and negative outputs and positive outputs and w/buffered output and medium power and medium speed |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Output Logic Form: |
| Resistor-transistor logic |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 buffer |
| Case Outline Source And Designator: |
| T0-99 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -4.0 volts power source and 4.0 volts power source |
| Time Rating Per Chacteristic: |
| 20.00 nanoseconds propagation delay time, low to high level output |
| Test Data Document: |
| 20886-252-112900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A458a0