

View Online at <https://aerobasegroup.com/nsn/5962-00-055-5322>

Body Length:

Between 0.240 inches and 0.275 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

48.8 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and low power and low power

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Diode-transistor logic

Input Circuit Pattern:

Triple 3 input

Design Function And Quantity:

3 gate, nand-nor

Case Outline Source And Designator:

T0-86 joint electron device engineering council

Time Rating Per Characteristic:

80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

12464-b77t0028 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0