NSN 5962-00-064-1693

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-064-1693

| view Offinite at https://aerobasegroup.com/hist//3302-00-004-1033 |
|---|
| Body Length: |
| Between 0.250 inches and 0.256 inches |
| Body Width: |
| Between 0.125 inches and 0.155 inches |
| Body Height: |
| Between 0.040 inches and 0.050 inches |
| Maximum Power Dissipation Rating: |
| 375.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Input Circuit Pattern: |
| 5 channel |
| Design Function And Quantity: |
| 1 switch, field effect transistor |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 30.0 volts power source |
| Test Data Document: |
| 96214-531815 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |