## NSN 5962-00-064-4050

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-064-4050

Body Length:
0.625 inches
Body Width:
0.350 inches
Body Height:
0.028 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and expandable and bipolar
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Resistor-transistor logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 gate, nor
2 gate, nor
2 gate, nor Terminal Surface Treatment:
2 gate, nor <b>Terminal Surface Treatment:</b> Solder
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: 
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:
2 gate, nor Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 4.5 volts power source Time Rating Per Chacteristic: 35.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig: