# NSN 5962-00-071-6908

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-071-6908

# **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

# **Body Height:**

Between 0.165 inches and 0.185 inches

# Maximum Power Dissipation Rating:

38.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+175.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and medium speed

#### **Inclosure Material:**

Glass and metal

#### Inclosure Configuration:

Can

## **Output Logic Form:**

Diode-transistor logic

## Input Circuit Pattern:

Dual 4 input

# **Design Function And Quantity:**

2 gate, nand

## Case Outline Source And Designator:

T0-101 joint electron device engineering council

## **Terminal Surface Treatment:**

Gold

## Voltage Rating And Type Per Characteristic:

10.0 volts power source

## **Precious Material And Location:**

Terminal surface gold

#### **Precious Material:**

Gold

## Test Data Document:

97942-128c076 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

#### Unit Of Measure:

- ---
- Demilitarization:
- Yes demil/mli

# **NSN 5962-00-071-6908** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

