NSN 5962-00-090-7226



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-090-7226 **Body Length:** 0.755 inches **Body Width:** Between 0.245 inches and 0.250 inches **Body Height:** 0.125 inches **Maximum Power Dissipation Rating:** 105.0 milliwatts **Operating Tempurature Range:** -20.0/+75.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **Features Provided:** Monolithic and positive outputs and w/decoded output **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 decoder, binary coded decimal to decimal **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

16152-24001110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0