NSN 5962-00-091-8931

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-091-8931

View Online at https://aerobasegroup.com/nsn/5962-00-091-8931
Body Length:
Between 0.360 inches and 0.410 inches
Body Width:
Between 0.240 inches and 0.275 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and positive outputs and adjustable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 regulator, voltage
Case Outline Source And Designator:
T0-87 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
40.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
82577-934173 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A458a0

Demilitarization: Yes - demil/mli