## NSN 5962-00-098-8721

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-098-8721

view Online at https://aerobasegroup.com/nsn/0302-00-030-0721
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and adjustable and positive outputs
nclosure Material:
Glass and metal
nclosure Configuration:
Can
nput Circuit Pattern:
2 input
Design Function And Quantity:
1 generator, function
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level
putput
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
97384-54000-90018 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
B pin
Shelf Life:
N/a

Yes - demil/mli

**Unit Of Measure:** 

Demilitarization:

## **NSN 5962-00-098-8721** Linear Microcircuit - Page 2 of 2



Fiig:

A458a0